

PRELIMINARY
DATASHEET

DESCRIPTION	SP3-GT35
Functions	<ul style="list-style-type: none"> • 3.5" LCD • Built in object library • 10 password levels • Modbus protocol
Display Type	8 bit color
Resolution in pixels h-v (inches)	320 x 240
Backlight	White LED backlight (20000 hr lamp life at 77 Deg F)
Contrast Adjustment	Via Software
Display Size (inches)	3.5" (diagonal)
User Memory	16 MB
Backup Memory	Upto 2 GB (micro SD)-Seperate module on PLC-optional
Serial Port - COM 1	RS232
Serial Port - COM 2	RS485
Serial Port - COM 3	Serial Printer Port
Function key	6 system keys
Operation Voltage	24VDC (-15% to +15%)
Backup Battery	3V lithium battery CR2032X1/ battery life:5 years
Real Time Clock (RTC)	Built-In
Operation Temperature	0 to 55 Deg C
Storage Temperature	-20 to 85 Deg C
Humidity (Non-condensing)	95% RH
Dimensions (W X H X D) mm	96 x 96 x 53
Cutout (W X H) mm	92 x 92
Safety Approval	CE, UL
Software	Windows based programing software
Order Code	SP3-GT35

Factory:

EL-27/1, Electronic Zone,
TTC Industrial Area,
MIDC, Mahape,
Navi Mumbai 400710,
INDIA,

Sales Office:

E-121, Ansa Industrial Estate,
Saki Vihar Road, Andheri (E),
Mumbai 400 072. INDIA
Tel.: +91-22-4039 4200/4202
Fax: +91-22-2847 1733
Tollfree: 1800 227353 (BSNL/MTNL only)
Email: sales@selec.com,

Selec Controls USA., Inc.:

203 main Street # 205
Flemington,
NJ 08822, U.S.A.
Phone: 908-627-2149,
Fax: 732-960-8611,
Email: usa@selec.com,
Web: www.seleccusa.com

Selec GmbH :

Mollwitzstrasse 2,
D-14059, Berlin,
Tel: +49 3030111870,
Fax.: +49 303011187-77,
Email: europe@selec.com
Web: www.selec-europe.com

Authorised Agent: