

## VENUS 10



### Product Information:

**VENUS-10W** – Recessed mounted LED downlighter in round shape designed with excellent thermally managed aluminium pressure die cast housing having heat dissipating fins for larger surface area, finished in epoxy powder coated white.

VENUS is featured with advanced mid power LEDs having high luminous efficacy and highly translucence frosted diffuser to ensure maximum light output with excellent glare control

Product Code	Rated Power (W)	Rated Voltage (V)	Input Current (A)	Weight (Kg)	Rated CCT (K)	CRI
LDRVS-10-C	10	240	0.05	0.4	6500	>70
LDRVS-10-N	10	240	0.05	0.4	4000	>70
LDRVS-10-W	10	240	0.05	0.4	3000	>70

### Electrical Specifications

Input Power:	10W
Operating Voltage range:	120-265V AC
Input Current:	0.05-0.08A
PF:	>0.9
THD:	<20%
Surge Protection:	3kV

### Specifications

Housing:	Aluminium pressure die cast
Optics:	opal diffuser
Mounting:	Spring loaded SS brackets provided for installation in the false ceiling.
Protection:	IP20
Rated Lumen:	900Lm (6500K)
Cut-out:	Φ145mm

### Applications

Commercial buildings | Hospitals | Residential buildings | Other indoor applications