

VENUS 20

DATA SHEET



Product Information:

VENUS-20W – Recessed mounted LED downlighter in round shape designed with excellent thermally managed aluminium pressure die cast housing having heat dissipating fins for larger surface area, finished in epoxy powder coated white.

VENUS is featured with advanced mid power LEDs having high luminous efficacy and highly translucence frosted diffuser to ensure maximum light output with excellent glare control

Product Code	Rated Power (W)	Rated Voltage (V)	Input Current (A)	Weight (Kg)	Rated CCT (K)	CRI
LDRVS-20-C	20	240	0.09	0.4	6500	>70
LDRVS-20-N	20	240	0.09	0.4	4000	>70
LDRVS-20-W	20	240	0.09	0.4	3000	>70

Electrical Specifications

Input Power:	20W
Operating Voltage range:	130-270 V AC
Input Current:	0.08-0.095 A
PF:	>0.95
THD:	<10%
Surge Protection:	3kV

Specifications

Housing:	Aluminium pressure die cast
Optics:	opal diffuser
Mounting:	Spring loaded SS brackets provided for installation in the false ceiling.
Protection:	IP20
Rated Lumen:	1700 Lm (6500K)
Cut-out:	Φ145mm

Applications

Commercial buildings | Hospitals | Residential buildings | Other indoor applications