



APEX 150

Product Information:

(CK BIRLA GROUP

APEX-150W - LED Highbay designed with excellent thermally managed aluminium pressure die cast housing having heat dissipating fins for larger surface area, satin finish powder coated in grey paint and fitted with polycarbonate cover in the front for the desired Ingress Protection.

APEX is featured with mid power LEDs having high luminous efficacy and coupled with advanced lens optics and high reflective aluminium reflector to get desired distribution with maximum light output

Product Code	Rated Power	Rated Voltage	Input Current	Rated CCT	CRI
	(W)	(V)	(A)	(K)	
LHAX-150-C	150	240	0.65	6000	>70

Electrical Specifications

Specifications

Input Power:	150W	Housing:	Aluminium pressure die cast housing	
Operating Voltage range:	120-280V AC			
Input Current:	0.64-0.66A	Front cover:	Polycarbonate cover	
PF:	>0.95	Optics:	Reflector	
THD:	<10%	Mounting:	I-bolt provided for chain suspension.	
Surge Protection:	4 KV	Protection:	IP65 (Lamp Compartment)	
		Rated Lumen:	15000Lm	

Applications

Warehouses I Industrial sheds I Hyper/supermarkets

Orient Electric: C-130 I Sector-63 I Noida-201301

TDS No: PLHB013 REV: 00 DATE: 21/11/2016