

# PINNACLE 190



## Product Information:

**PINNACLE-190W** LED Highbay designed with excellent thermally managed aluminium die cast housing having heat dissipating fins for larger surface area, satin finish powder coated in grey paint and fitted with toughened glass in the front for the desired Ingress Protection.

PINNACLE is featured with high power LEDs having high luminous efficacy and high purity aluminium reflector to ensure maximum light output.

Product Code	Rated Power (W)	Rated Voltage (V)	Input Current (A)	Rated CCT (K)	CRI
LHPN-190-C-90D	190	240	0.83	6000	>70
LHPN-190-C-60D	190	240	0.83	6000	>70

## Electrical Specifications

Input Power:	190W
Operating Voltage range:	120-280V AC
Input Current:	0.79-0.87A
PF:	>0.95
THD:	<10%
Surge Protection:	4kV Internal 10KV External

## Specifications

Housing:	Aluminum pressure die cast
Front cover:	Toughened glass
Optics:	Lens
Beam angle :	90 degree /60 degree
Mounting:	Bracket provided for chain suspension or surface mounting.
Protection:	IP65
Rated Lumen:	21300Lm

## Applications

Warehouses | Industrial sheds | Hyper/supermarkets

Orient Electric: C-130 | Sector-63 | Noida-201301