







Product Information:

FIESTA-60W - LED streetlight designed with excellent thermally managed aluminium pressure die cast housing having heat dissipating fins for larger surface area, satin finish powder coated in grey paint and fitted with toughened glass in the front for the desired Ingress Protection.

FIESTA is featured with high power LEDs having high luminous efficacy and coupled with advanced optics for Batwing light distribution that provides improved uniformity in horizontal and vertical directions and excellent glare control.

Product Code	Rated Power (W)	Rated Voltage (V)	Input Current (A)	LED make	Rated CCT (K)	CRI
LSFS-060-C	60	240	0.28	Nichia	5700	>70

Electrical Specifications

Specifications

Input Power: 60W Housing: Aluminium pressure die cast Operating Voltage range: 120-265V AC Front cover: Toughened glass Input Current: 0.25-0.28A

Optics: Lens (PC) PF: >0.9 Mounting: In-built pole entry for 50 mm OD

pipe. THD: 12%

IP65 Protection: Surge Protection: 4kV Internal

> 10 KV External Batwing (135⁰/85⁰) Distribution:

> > Rated Lumen: 5400Lm

Applications

Road lighting I Campus lighting I Industrial estates I Open parkings I Circulating areas

TDS No: PLST009 REV: 00 DATE:15/09/2015