

# AQUA 36



## Product Information:

**AQUA-36W** – The LED 2x2 tile is a recessed mounted general lighting solution for offices which offers excellent energy saving and maintenance-free operation. This product is featured with advanced LED light sources having high luminous efficacy and highly transluence optical system to ensure maximum light output with excellent glare control and uniformity.

AQUA has a unique design of opal diffuser with large window for wider and more uniform illumination on the working plane.

Product Code	Rated Power (W)	Rated Voltage (V)	Input Current (A)	Weight (Kg)	Rated CCT (K)	CRI
LTRAQ-36-C	36	240	0.16	3.5	6000	>80
LTRAQ-36-N	36	240	0.16	3.5	4000	>80

### Electrical Specifications

Input Power:	36W
Operating Voltage range:	130-277V AC
Input Current:	0.14-0.17A
PF:	>0.9
THD:	<20%
Surge Protection:	2kV

### Specifications

Housing:	CRCA, white powder coated
Optics:	Frosted opal diffuser
Mounting:	Suitable for Recess mounting in Modular grid ceiling and POP/Gypsum ceiling
Protection:	IP20
Rated Lumen:	3060 Lm (6000K)
Cut-out:	580 x 580mm (for POP/Gypsum ceiling)

### Applications

Offices | BPOs | Hospitals | Banks | Meeting rooms | Other indoor applications