



Product Information:

UDline- The seamless aluminium extruded suspended up/downlight luminaire for indoor architectural lighting solution offers excellent energy saving and maintenance-free operation. This product is featured with best in class LED light sources having high luminous efficacy and highly transluence optical system to ensure maximum light output with excellent glare control and uniformity.

- ✓ UDline can be easily connected end to end to make a continuous lighting system of any length.
- ✓ UDline is also available in 'downlight only' version

Product Code	Rated Power (W)	Rated Voltage (V)	Input Current (A)	Size (LxWxH)mm	Rated CCT (K)	CRI
LCPUD-28-C	8+20	240	0.12	1200x54x70	6000	>80
LCPUD-28-N	8+20	240	0.12	1200x54x70	4000	>80

Electrical Specifications

Input Power: 28W
 Operating Voltage range: 130-265V AC
 Input Current: 0.11-0.14A
 PF: >0.95
 THD: <20%
 Surge Protection: 2kV

Specifications

Housing: Aluminium Extruded, White powder coated
 Optics: Frosted PMMA diffuser
 Mounting: Suspension system with 1.5mtr string and safety height adjustable system provided for pendant mounting. Work with all kinds of ceiling types
 Protection: IP20
 Rated Lumen: 2380Lm

Applications

Offices | BPOs | Meeting rooms | Other indoor applications